

ACCESSORI GRADO 80 / GRADE 80 ACCESSORIES

Catena secondo norma EN 818-4 / Chain according to EN 818-4

| CATENA SECONDO NORMA EN 818-2 CHAIN ACCORDING TO EN 818-2 | | | | | | | | | | | |
|--|-------|-------------------------|----|-------------------------|--------|--------|----------------|----------------------------------|--------|--------|-------|
| Catena Chain | | Tolleranza Tolerance | P | Tolleranza Tolerance | Li min | Le max | Peso Weight | Portata Working load limit | M.P.F. | B.F. | f min |
| Ø mm | inch | mm | mm | mm | mm | mm | kg/m | kg | KN | KN | mm |
| 6 | 1/4 | ±0,24 | 18 | ±0,5 | 7,8 | 22,2 | 0,8 | 1120 | 28,3 | 45,2 | 4,8 |
| 7 | 9/32 | ±0,28 | 21 | ±0,6 | 9,1 | 25,9 | 1,1 | 1500 | 38,5 | 61,6 | 5,6 |
| 8 | 5/16 | ±0,32 | 24 | ±0,7 | 10,4 | 29,6 | 1,4 | 2000 | 50,3 | 80,4 | 6,4 |
| 10 | 3/8 | ±0,40 | 30 | ±0,9 | 13,0 | 37,0 | 2,2 | 3150 | 78,5 | 126,0 | 8,0 |
| 13 | 1/2 | ±0,52 | 39 | ±1,2 | 16,9 | 48,1 | 3,8 | 5300 | 133,0 | 212,0 | 10,0 |
| 16 | 5/8 | ±0,64 | 48 | ±1,4 | 20,8 | 59,2 | 5,7 | 8000 | 201,0 | 322,0 | 13,0 |
| 20 | 3/4 | ±1,00 | 60 | ±1,8 | 26,0 | 74,0 | 9,0 | 12500 | 314,0 | 503,0 | 16,0 |
| 22 | 7/8 | ±1,10 | 66 | ±2,0 | 28,6 | 81,4 | 10,9 | 15000 | 380,0 | 608,0 | 18,0 |
| 26 | 1 | ±1,30 | 78 | ±2,3 | 33,8 | 96,2 | 15,2 | 21200 | 531,0 | 849,0 | 21,0 |
| 32 | 1 1/4 | ±1,60 | 96 | ±2,9 | 41,6 | 118,0 | 23,0 | 31500 | 804,0 | 1290,0 | 26,0 |

