

BRACHE IN FUNE ANIMA METALLICA / WIRE ROPE SLING - METALLIC CORE

Tirante in fune Anima Metallica Wire rope slings - metallic core						
Ø Fune/Rope (mm)	Carico massimo di utilizzazione Maximum working load				d Max	Asole/Eyes AxB (mm)
	I	U	60°	90°		
8	740	1480	1280	1050	24	64x128
10	1160	2320	2010	1640	28	80x160
12	1660	3320	2870	2350	30	96x192
14	2280	4560	3950	3220	36	112x224
16	2950	5900	5110	4170	38	128x256
18	3740	7480	6480	5290	45	144x288
20	4620	9240	8000	6530	50	160x320
22	5600	11200	9700	7920	56	176x352
24	6660	13320	11530	9420	62	192x384
26	7820	15640	13540	11060	70	208x416
28	9070	18140	15710	12830	75	224x448
30	10790	21580	18680	15260	80	240x480
32	11840	23680	20500	16750	95	256x512
34	13510	27020	23390	19110	100	272x544
36	14990	29980	25960	21200	110	288x576
40	18540	37080	32100	26220	120	320x640
44	22390	44780	38770	31670	150	352x704
48	26610	53220	46080	37640	160	224x768
52	31200	62400	54030	44130	170	416x832
56	36640	72680	62930	51400	170	456x912
60	41660	83320	72140	58930	180	480x960

