

BRACHE IN FUNE ANIMA TESSILE / WIRE ROPE SLING - FIBER CORE

| Brache in fune anima tessile Wire rope slings - fiber core | | | | | | |
|---|---|-------|-------|-------|----------|------------------------|
| Ø Fune/Rope (mm) | Carico massimo di utilizzazione Maximum working load | | | | Ø Max | Asole/Eyes AxB (mm) |
| | I | U | 60° | 90° | | |
| 4 | 160 | 320 | 280 | 230 | 14 | 50x100 |
| 5 | 250 | 500 | 430 | 350 | 16 | 50x100 |
| 6 | 390 | 780 | 680 | 550 | 18 | 50x100 |
| 7 | 520 | 1040 | 900 | 740 | 20 | 56x112 |
| 8 | 700 | 1400 | 1210 | 990 | 24 | 64x128 |
| 9 | 870 | 1740 | 1510 | 1230 | 24 | 72x144 |
| 10 | 1070 | 2140 | 1850 | 1510 | 28 | 80x160 |
| 11 | 1300 | 2600 | 2250 | 1840 | 28 | 88x176 |
| 12 | 1540 | 3080 | 2670 | 2180 | 30 | 96x192 |
| 13 | 1810 | 3620 | 3130 | 2560 | 32 | 104x208 |
| 14 | 2090 | 4180 | 3620 | 2960 | 36 | 112x224 |
| 16 | 2750 | 5500 | 4760 | 3890 | 38 | 128x256 |
| 18 | 3500 | 7000 | 6060 | 4950 | 45 | 144x288 |
| 20 | 4290 | 8580 | 7430 | 6070 | 50 | 160x320 |
| 22 | 5190 | 10380 | 8990 | 7340 | 56 | 176x352 |
| 24 | 6170 | 12340 | 10680 | 8730 | 62 | 192x384 |
| 26 | 7250 | 14500 | 12550 | 10250 | 70 | 208x416 |
| 28 | 8410 | 16820 | 14560 | 11900 | 75 | 224x448 |
| 30 | 10000 | 20000 | 17320 | 14140 | 80 | 240x480 |
| 32 | 11000 | 22000 | 19050 | 15560 | 95 | 256x512 |
| 34 | 12370 | 24740 | 21420 | 17500 | 100 | 272x544 |
| 36 | 13890 | 27780 | 24050 | 19650 | 110 | 288x576 |
| 40 | 17160 | 34320 | 29710 | 24270 | 120 | 320x640 |

